

MTL200

IOT GATEWAY



- * **Multifunctional for all IoT applications**
- * **0,961 OLED**
- * **Suitable for all One Wire sensors**
- * **Internet connection via Ethernet, WiFi, or 2G/4G**
- * **RS232 / RS485 / Canbus serial interfaces**
- * **Rich analog and digital inputs / outputs**
- * **Wireless local communication (ISM & BLE)**
- * **All features are configurable over WiFi**
- * **Compatible with MQTT or BIOSTURK protocol**
- * **Wired and/or wireless sensor connections**
- * **Monitoring via WEB or mobile phones**
- * **Remote update for SW and settings**
- * **GPS**
- * **CE**
- * **Bakup battery**



TECHNICAL SPECIFICATIONS

COMMUNICATION

WiFi 802.11 b/g/n
BLE 4.2
TCP-IP or UDP Ethernet (Optional)
2G /4G (Optional)
RF ISM (Optional)
GPS (Optional)

PROCESSOR

Xtensa 32bit LXG
2Mb Flash

ELECTRICAL

Power: +9V to +36VDC

MOTION SENSOR

3 axis motion sensor (Optional)

INTERFACES

3 x DI, 2 x DO, 2 x 1W, 1 x AI
RS485, RS232, Canbus

OPERATING TEMPERATURE

0°C to +45°C

PHYSICAL

Dimensions (LxWxH): 125,5 x 116 x 33mm
Weight: 90g

ACCESSORIES

0,96" OLED
LiPo Backup Battery
RFID Reader
Temperature sensor
Humidity sensor
Smoke detector
CO sensor
PIR detector
JPEG Camera
Flood sensor
Panic button
IR Controller
BMS of batteries



BIOSTURK.COM

MTL200_EN_V1.0

Technical specifications are subject to change without notice.